
System No. W-L-1001

F Ratings -- 1, 2, 3 and 4 Hr (See Items 2 and 3)

T Ratings -- 0, 1, 2, 3, and 4 Hr (See Item 3)

L Rating At Ambient — less than 1 CFM/sq ft

L Rating At 400 F - less than 1 CFM/sq ft



1. Wall Assembly -- The 1, 2, 3 or 4 hr fire-rated gypsum wallboard/stud wall assembly shall be constructed of the materials and in the manner described in the individual U300 or U400 Series Wall or Partition Designs in the UL Fire Resistance Directory and shall include the following construction features:

A. Studs -- Wall framing may consist of either wood studs (max 2 h fire rated assemblies) or steel channel studs. Wood studs to consist of nom 2 by 4 in. lumber spaced 16 in. OC with nom 2 by 4 in. lumber end plates and cross braces. Steel studs to be min 3-5/8 in. wide by 1-3/8 in. deep channels spaced max 24 in. OC.

B. Gypsum Board* -- Nom 1/2 or 5/8 in. thick, 4 ft. wide with square or tapered edges. The gypsum wallboard type, thickness, number of layers, fastener type and sheet orientation shall be as specified in the individual U300 or U400 Series Design in the UL Fire Resistance Directory. Max

2. Through-Penetrant -- One metallic pipe, conduit or tubing installed either concentrically or eccentrically within the firestop system. The annular space between pipe, conduit, or tubing and periphery of opening shall be min of 0 in. (point contact) to max 2 in. Pipe, conduit or tubing to be rigidly supported on both sides of wall assembly. The following types and sizes of metallic pipes, conduits or tubing may be used:

A. Steel Pipe -- Nom 24 in. diam (or smaller) Schedule 10 (or heavier) steel pipe.

B. Iron Pipe -- Nom 24 in. diam (or smaller) service weight (or heavier) cast iron soil pipe, nom 12 in. diam (or smaller) or Class 50 (or heavier) ductile iron pressure pipe.

C. Conduit -- Nom 6 in. diam (or smaller) steel conduit or nom 4 in. diam (or smaller) steel electrical metallic tubing.

D. Copper Tubing -- Nom 6 in. diam (or smaller) Type L (or heavier) copper tubing.

E. Copper Pipe -- Nom 6 in. diam (or smaller) Regular (or heavier) copper pipe.

F. Through Penetrating Product -- Flexible Metal Piping --

The following types of steel flexible metal gas piping may be used:

1. Nom 2 in. diam (or smaller) steel flexible metal gas piping. Plastic covering on piping may or may not be removed on both sides of floor or wall assembly.

OMEGA FLEX INC

2. Nom 1 in. diam (or smaller) steel flexible metal gas piping. Plastic covering on piping may or may not be removed on both sides of floor or wall assembly.

GASTITE, DIV OF TITEFLEX

3. Nom 1 in. diam (or smaller) steel flexible metal gas piping. Plastic covering on piping may or may not be removed on both sides of floor or wall assembly.

WARD MFG LLC

Fill, Void or Cavity Material* -- Caulk or Sealant -- Min 5/8, 1-1/4, 1-7/8 and 2-1/2 in. thickness of caulk for 1, 2, 3 and 4 hr rated assemblies, respectively, applied within annulus, flush with both surfaces of wall. Min 1/4 in. diam bead of caulk applied to gypsum board/penetrant interface at point contact location on both sides of wall. The hourly F Rating of the firestop system is dependent upon the hourly fire rating of the wall assembly in which it is installed, as shown in the following table. The hourly T Rating of the firestop system is dependent upon the type or size of the pipe or conduit and the hourly fire rating of the wall assembly in which it is installed, as tabulated below:

Max Pipe or Conduit Diam In	F RATING Hr	T RATING Hr
1	1 or 2	0+, 1 or 2
1	3 or 4	3 or 4
4	1 or 2	0
6	3 or 4	0
12	1 or 2	0

+When copper pipe is used, T Rating is 0 hr.

3M COMPANY -- CP 25WB+ or FB-3000 WT.

*Bearing the UL Classification Mark

DIVISION 16 - FIRE ALARM

PART 1 - GENERAL

1.1 DESCRIPTION OF THE WORK

A. Work under this section includes, but is not necessarily limited to, furnishing and installing the following: Fire alarm panel, wiring and devices

B. All work shall be complete and items, equipment, etc., shall be electrically connected for proper and correct

C. All work under this contract shall be installed in accordance with the latest edition of the following codes and standards insofar as they apply:

1. The 2017 National Electrical Code.

2. NFPA 72

3. Underwriter's Laboratories, Inc., Standards and approved listings.

4. Electrical Testing Labatories standards. 5. North Carolina Building Code, Latest Edition and Revisions. 6. All local codes and ordinances.

D. The Fire Alarm Contractor shall be licensed in the State of North Carolina and have all local licenses required for the

E. Obtain all permits, licenses, inspections, etc., required for the work and pay for the same. Furnish final certificate of inspection and approval from the electrical inspector having jurisdiction prior to acceptance of the work. F. All work shall be done by skilled mechanics and shall

present a neat, trim, workmanlike condition when complete.

1.2 INTENT A. The intent of these specifications and the accompanying drawings is to convey as reasonably as possible the requirements for a complete job ready for the building to operate. The Fire Alarm Contractor shall take this into consideration and include in his base bid allowance for contingencies as will allow him to provide minor pieces of equipment and labor not specifically indicated but

required for the job to operate properly, at no additional cost

to the Owner. 1.3 COORDINATION

A. Coordinate work with other contractors. Notify Architect of apparent conflicts early to expedite construction. If structural damage appears imminent, stop work and notify Architect for a decision before resuming operations.

B. Locations shown are approximate. The drawings do not give exact details as to elevations and locations of various pipes, fittings, ducts, conduit, etc., and do not show all offsets and other installation details which may be required. Coordinate all locations with architect before any rough-in.

1.4 SHOP DRAWINGS

A. Provide complete shop drawings per NCSFC section 907.1.2 to the local

fire marshal prior to start of construction including: 1. Floorplan with room names

2. Location of all FA devices 3. Location of panels

4. Power connections

5. Battery calculations 6. Conductors types and sizes 7. Voltages drop calculations 8. Equipment cut—sheets, model numbers, etc.

PART 2 - PRODUCTS AND MATERIALS

A. All material shall be new and shall bear the manufacturer's name, trade name, and UL label where such standard has been established for the particular material. Materials shall be the standard products of manufacturer's regularly engaged in the manufacturer of the required type of equipment and the manufacturer's latest approved design.

1. Boxes installed in concealed locations shall be set flush with

the finished surfaces. 2. Provide rated boxes in all fire barriers & walls installed per code.

PART 3 - EXECUTION

3.1 FIRE ALARM SYSTEM EQUIPMENT

A. Provide a complete operable fire alarm system as shown on the drawings and as required by State, and Local codes.

B. The main control panel is existing. The unit is an addressable type. Verify spare

capacity is available prior to bid. Expand as required. C. Provide a remote key test switch for the duct detectors. Locate as


directed by the local AHJ. D. All fire alarm system cables shall be installed in conduit. Size as required by the equipment supplier. Provide a submittal of all devices and a riser diagram for approval before installation of any equipment.


E. The return air smoke detectors will be furnished by the E.C. to the HVAC contractor for installation. The HVAC contr shall be responsible for the shut down of all AHU'S. The E.C. shall be responsible for all connections to the fire alarm controller.

3.2 CLEAN UP


A. During construction, keep the site clean of debris. Upon completion, and before final inspection, clean up the premises to remove all evidence of work. In addition upon completion of construction leave equipment clean. 3.3 GUARANTEE

A. Guarantee all materials and labor included in the fire alarm work for a period of one year from date of final acceptance by the Owner. Any part or parts of the work or equipment which prove to be defective during the guarantee period shall be replaced at no additional cost to the Owner.









SEE PLAN FOR ACTUAL

PARTIAL FIRE ALARM RISER FA-I SCALE: NTS

Planning

Coastal



Member of the Americar Institure of Architects

Lee D. Dixon, Jr., AIA

252-247-2127 lee@coastalarchitecture.ne 4206 Bridges St. Ext., Suite C

Morehead City, NC 28557

0 OUR

E SQ. AROI 9 H 0 0

C



FIRE ALARM SPECS & RISER

WG BY: RM BEB CKD BY: REVISIONS

ENGINEER

3305–109 DURHAM DRIVE BURKE DESIGN GROUP RALEIGH, NC 27603 PHONE: (919) 771–1916 FAX: (919) 779-0826 email: ben@bdg-nc.com Corp. License # C-2652

SHEET NO.

NOTE:
THE EXISTING INFORMATION SHOWN ON THIS SHEET IS FROM SHELL PERMIT DRAWINGS.
THE CONTRACTOR IS RESPONSIBLE FOR VISITING THE SITE AND FIELD VERIFYING ALL RELEVANT INFORMATION.
THE SUBMISSION OF A BID INDICATES ACCEPTANCE OF EXISTING CONDITIONS.
NOTIFY THE ENGINEER OF ANY DISCREPANCIES NOTED. _ -- -- -- --GENERAL FIRE ALARM NOTES: 1 HORN/STROBES MUST BE WITHIN 15'-0" OF THE END OF EACH CORRIDOR. PROVIDE STROBES IN ALL CORRIDORS, BATHROOMS, BREAK ROOMS AND STORAGE AREAS. INSTALL PER ADA. 2 CANDELA RATINGS SHOULD BE LABELED ON ALL STROBES. 3 ALL STROBES WITHIN SIGHT OF EACH OTHER MUST BE SYNCHRONIZED PER NFPA 72 UNLESS MAXIMUM REQUIRED SEPARATION 4 THE MAIN FIRE ALARM PANEL IS LOCATED IN THE CLERKS OFFICE. VERIFY. 5 VERIFY THAT A SD IS ADJACENT TO THE FACP. 6 ALL EXPOSED WIRE SHALL BE IN CONDUIT. PLENUM RATED CABLE MAY BE USED WHERE CONCEALED IN ALL AREAS EXCEPT ASSEMBLY AREAS. ALL WIRING IN ASSEMBLY AREAS MUST BE IN CONDUIT. 7 ALL DEVICES, PANELS, ETC MUST BE BY SAME MANUFACTURER AND COMPATIBLE NOTE: VERIFY HEIGHT/LOCATION OF ALL DEVICES PRIOR TO INSTALLATION. PROVIDE ALL ITEMS REQUIRED FOR A COMPLETE SYSTEM MEETING ALL CODES. BASEMENT FA PLAN 8 ALL WORK MUST MEET NFPA 72 AND APPLICABLE LOCAL CODES AND ORDINANCES. COORDINATE THE INSTALLATION WITH THE LOCAL FIRE MARSHALL. FA-2.1 SCALE: 1/8"=1'-0" PROVIDE DUCT SMOKE DETECTORS WITH ALL HVAC EQUIP OVER 5 TONS IN SIZE (EXISTING & NEW). 9 MOUNT WALL-MOUNT HORN STROBES SUCH THAT THE ENTIRE LENS IS NOT LESS THAN 80" AND NOT GREATER THAN 96" ABOVE THE FINISHED FLOOR. 10 MOUNT MANUAL PULL STATIONS SUCH THAT THE OPERABLE PART OF THE DEVICE IS NOT LESS THAN 42" AFF AND NOT MORE THAN 54" AFF.

Coastal

Architectural Planning



Member of the Americar Institure of Architects

Lee D. Dixon, Jr., AIA

252-247-2127

lee@coastalarchitecture.net

4206 Bridges St. Ext., Suite C Morehead City, NC 28557 www.CoastalArchitecture.net

COURTHOUSE COUNTY

113 COURTHOUSE SQ. VHITEVILLE, NORTH CAROLINA

FIRE ALARM PLAN


DWG BY: RM CKD BY: **BEB** REVISIONS

ENGINEER

BURICE DESIGN GROUP

3305-109 DURHAM DRIVE RALEIGH, NC 27603 PHONE: (919) 771-1916

SHEET NO. FAX: (919) //9-0023 email: ben@bdg-nc.com Corp. License # C-2652



Coastal Architecture

Architectural Design Planning Interiors



Member of the Americar Institure of Architects

Lee D. Dixon, Jr., AIA
252-247-2127
lee@coastalarchitecture.net

4206 Bridges St. Ext., Suite C Morehead City, NC

COURTHOUSE

COUNTY MUS

0

C




FIRST FLOOR FIRE ALARM PLAN

SUED: **8/15/2022** DWG BY: RM CKD BY: **BEB** REVISIONS



Corp. License # C-2652

SHEET NO.



GENERAL FIRE ALARM NOTES:

- 1 HORN/STROBES MUST BE WITHIN 15'-0" OF THE END OF EACH CORRIDOR. PROVÍDE STROBES IN ALL CORRIDORS, BATHROOMS, BREAK ROOMS
- AND STORAGE AREAS. INSTALL PER ADA. 2 CANDELA RATINGS SHOULD BE LABELED ON ALL STROBES.
- 3 ALL STROBES WITHIN SIGHT OF EACH OTHER MUST BE SYNCHRONIZED PER NFPA 72 UNLESS MAXIMUM REQUIRED SEPARATION
- IS OBTAINED. 4 THE MAIN FIRE ALARM PANEL IS LOCATED IN THE CLERKS OFFICE. VERIFY.
- 5 VERIFY THAT A SD IS ADJACENT TO THE FACP.
- 6 ALL EXPOSED WIRE SHALL BE IN CONDUIT. PLENUM RATED CABLE MAY BE USED WHERE CONCEALED IN ALL AREAS EXCEPT ASSEMBLY AREAS. ALL WIRING IN ASSEMBLY AREAS MUST BE IN CONDUIT.
- 7 ALL DEVICES, PANELS, ETC MUST BE BY SAME MANUFACTURER AND COMPATIBLE PROVIDE ALL ITEMS REQUIRED FOR A COMPLETE SYSTEM MEETING ALL CODES.
- 8 ALL WORK MUST MEET NFPA 72 AND APPLICABLE LOCAL CODES AND ORDINANCES. COORDINATE THE INSTALLATION WITH THE LOCAL FIRE MARSHALL.
- 9 MOUNT WALL-MOUNT HORN STROBES SUCH THAT THE ENTIRE LENS IS NOT LESS THAN 80" AND NOT GREATER THAN 96" ABOVE THE FINISHED FLOOR.
- 10 MOUNT MANUAL PULL STATIONS SUCH THAT THE OPERABLE PART OF THE DEVICE IS NOT LESS THAN 42" AFF AND NOT MORE THAN 54" AFF.



VERIFY HEIGHT/LOCATION OF ALL DEVICES PRIOR TO INSTALLATION. PROVIDE DUCT SMOKE DETECTORS WITH ALL HVAC EQUIP OVER 5 TONS IN SIZE (EXISTING & NEW). Coastal

Architectural Design Planning



Member of the Americar Institure of Architects

Lee D. Dixon, Jr., AIA
252-247-2127
lee@coastalarchitecture.net 4206 Bridges St. Ext., Suite C Morehead City, NC 2885 CoastalArchitecture not

S OURTHOU 113 COURTHOUSE EVILLE, NORTH CA

SECOND FLOOR FIRE ALARM PLAN

19035 SUED: **8/15/2022** DWG BY: RM CKD BY: **BEB** REVISIONS

ENGINEER

BURICE DESIGN GROUP

3305-109 DURHAM DRIVE RALEIGH, NC 27603 PHONE: (919) 771-1916 FAX: (919) 779-0826
email: ben@bdg-nc.com Corp. License # C-2652

SHEET NO.